



Model NO.	CTSRDNA200
Camera	
Image Sensor	IMX222
Main processor	A5S66
Resolution	1080P
Effective Pixels	1920(H)*1080(V)
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec
Sync System	External
Usable Illumination	0.01Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Lens	
Focus Length	Board Lens 3.6mm/F2.0
Focus Control	Fixed
Lens Type	Fixed
Pixels	3M Pixels
Night Vision	
Infrared LED	Φ 5X24PCS
Infrared Distance	20M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

Network	
Ethernet	RJ-45 (10/100Base-T)

Protocol	IPv4, HTTP, TCP/IP, FTP, NTP, RTSP, UDP, SMTP, DNS, DDNS
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
WIFI	N/A
Video Delay	0.3S (Within the Lan)
Main Stream	1920*1080@30fps
Sub Stream	704*576@30fps, 352*288@30fps
IE Brower	IE6-11, Google Chrome(IE Tab), Firefox(IE Tab)
Smart Phone	iPhone, iPad, Android, Android Pad

Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Compression	H.264/JPEG,Support record AVI format.
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
WDR	YES
Recording Mode	NVR/NAS/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian
General	
Housing	Vandalproof(metal)
Lens Angle Adjustment	No, Without Bracket
IR Cut Filter	YES
Operation Temperature	-10 ~ +50 RH95% Max
Storage Temperature	-20 ~ +60 RH95% Max
Power Source	DC12V±10%, 500mA

Dimension	Φ 94 x 69(H)mm
Weight	450g